
gettext.js Documentation

Release 1.0

Jonas Obrist

Jan 26, 2018

Contents

1	Installation	3
1.1	Installation	3
2	Usage	5
2.1	Workflow	5
2.2	Transpile using CLI	5
2.3	Webpack	5
2.4	Using transpiled files	5
3	Reference	7
4	Changelog	9
4.1	2.0.0	9
4.2	1.2	9
4.3	1.1	9
4.4	1.0	10
5	Indices and tables	11

gettext.js provides a GNU gettext like interface for use in browsers, a MO file to JS transpiler and a webpack loader for MO files.

CHAPTER 1

Installation

1.1 Installation

yarn add gettextjs

2.1 Workflow

1. Create your po files using your current workflow.
2. Create your mo files using your current workflow.
3. **Choose one of the following:**
 - (a) Transpile your mo files to js files using *gettextjs*
 - (b) Import your mo files in js and use the webpack loader.

2.2 Transpile using CLI

Transpile all your MO files to JS using *gettextjs <input> <output>*.

Note that the resulting code is ES7 code (including *import*) and needs to be transpiled before used.

2.3 Webpack

Add the *gettextjs/dist/loader* loader to your webpack config for mo files:

The *babel-loader* is needed because the *gettextjs* loader outputs ES7, but you can use another loader to do the JS->JS transpilation.

2.4 Using transpiled files

The transpiled files have a default export which is an instance of *Translations()*. They can either be used directly or you can call *set_catalog()* with the instance.

`gettext()` and `ngettext()` are equivalent to `gettext(3)` and `ngettext(3)`. `gettext()` takes a single `msgid` and returns the translation for it, if it finds one, or the `msgid`. `ngettext()` is used for translations which may have plurals.

class `Translations` (*headers, messages, plural*)

Arguments

- **string** `headers` (*Immutable.Map<string,>*) – MO headers.
- **Immutable.List<string>>** `messages` (*Immutable.Map<string,>*) – The translations.
- **=> number plural** (*(number)*) – Function to resolve plural forms.

Usually this class should not be created manually.

`Translations.gettext` (*msgid*)

Arguments

- **msgid** (*string*) – Message ID to look up.

Returns Translated string (or input string if not found).

`Translations.ngettext` (*msgid, msgid_plural, count*)

Arguments

- **msgid** (*string*) – Message ID for the singular string.
- **msgid_plural** (*string*) – Message ID for the plural string.
- **count** (*number*) – Used to detect whether plural or singular form should be used.

Returns Translated string (or one of the input strings if not found).

set_catalog (*catalog*)

Arguments

- **catalog** (*Gettext*) –

Set a translation as the currently active, global translations.

gettext (*msgid*)

Arguments

- **msgid**(*string*) – Message ID to look up.

Returns Translated string (or input string if not found).

Uses the translations set by `set_catalog()` to translate a message ID.

ngettext(*msgid*, *msgid_plural*, *count*)

Arguments

- **msgid**(*string*) – Message ID for the singular string.
- **msgid_plural**(*string*) – Message ID for the plural string.
- **count**(*number*) – Used to detect whether plural or singular form should be used.

Returns Translated string (or one of the input strings if not found).

Uses the translations set by `set_catalog()` to translate a message ID.

4.1 2.0.0

Release data: January 26, 2018

- Re-wrote the whole library.
- Ported MO->JS transpiler to Javascript.
- Added webpack loader to load MO files directly in you sources.
- Removed dependency on `eval` and `new Function`.
- Renamed `gettext.Gettext` to `gettext.Translations`.

4.2 1.2

Release date: January 20, 2017

- Removed `eval` from Javascript runtime.
- Use `yarn` for development Javascript dependencies.

4.3 1.1

Release date: September 24, 2016

- Made the JavaScript runtime an NPM package.
- Removed the `Gettext.load` API. If you want to load catalogs via AJAX, please use the AJAX library of your choice.
- Added “global” APIs `set_catalog()`, `gettext()` and `ngettext()`.

- Removed docopt as a dependency for the compiler. The compiler now only depends on Python 3.5.

4.4 1.0

Release date: Dec 25, 2015

- Initial release.

CHAPTER 5

Indices and tables

- `genindex`
- `modindex`
- `search`

G

`gettext()` (built-in function), [7](#)

N

`ngettext()` (built-in function), [8](#)

S

`set_catalog()` (built-in function), [7](#)

T

`Translations()` (class), [7](#)